

  
**ICOM**

VHF MARINE TRANSCEIVER

**IC-M73EURO**

***Slim, Stylish, Powerful VHF  
with Professional Features***



**Last Call Voice  
Recording\***

The last call voice recording function automatically saves the last incoming call for 1 minute. You can also start recording manually. You will not miss an important call.



**Active Noise Cancelling  
Technology\***

The built-in bidirectional active noise cancelling reduces background noise to up to 90% and improves both your transmitted voice and incoming call. You will hear better and clearer!



**Bass Boost  
Function\***

The signal processing technology emphasizes low-pitched sound to provide a rich bass sound for both transmit and receive signals.



**700mW  
Loud Audio**



**6W RF  
Output Power**



**IPX8 Advanced  
Waterproofing**

\* Basic version (no voice recorder, no noise canceller and no bass boost function) available for limited markets.

## 700mW Loud Audio

The IC-M73EURO uses a BTL (bridged load) amplifier that doubles the audio output. Its internal speaker delivers a loud 700mW audio output with clear sound.

## 6W RF Output Power

The IC-M73EURO's 6 Watts\*1 of transmit power will provide extended communication range for the user. A large capacity Lithium-Ion battery allows for 18 hours of operation, under normal conditions\*2.

\*1 1W for FRG version, \*2 Typical operation with 5:5:90 duty ratio.

## IPX8 Advanced Waterproofing

The IC-M73EURO continues to offer Icom's best waterproof protection. The radio has been tested to survive after being submersed in 1.5m (4.9ft) depth of water for 30 minutes.

## Slim, Hourglass Body Wide Viewing Angle LCD

The IC-M73EURO has a stylish, ergonomic design. A durable and rugged body provides for user-friendly operation and long life. A wide viewing angle, high intensity LCD offers bright, easy to read characters.

## Additional features

- AquaQuake™ water draining function
- Dual/Tri-Watch function for monitoring Channel 16 and/or call channel
- 4 level battery indicator
- Favorite channel and tag scan functions
- Optional waterproof speaker-microphones, HM-167 and HM-202
- Rapid charger BC-210 supplied
- Auto power save function
- FA-S64V short antenna

## SPECIFICATIONS

GENERAL		
Frequency range	Tx	156.000-161.450MHz
	Rx	156.000-163.425MHz
Usable channel groups	INT, USA* channels (* Depending on version)	
Type of emission	16K0G3E (FM)	
Current drain (at 7.4V DC)		
Tx 6W output	1.5A	
Rx Max. audio (int SP/Ext SP)	450mA/250mA	
Operating temp. range	-15°C to +55°C	
Antenna impedance	50Ω (SMA)	
Dimensions (WxHxD) (projections not included)	52.5x125x30 mm	
Weight (approx.)	320g (With BP-245N, FA-S64V, MB-103)	

Measurements made in accordance with EN301-178-2. All stated specifications are subject to change without notice or obligation.

TRANSMITTER	
Output power (Hi/Mid/Low)	6W/3W/1W 1/0.5W (FRG version)
Max. frequency deviation	±5.0kHz
Frequency stability	±1.5kHz
Spurious emissions	0.25µW
Adjacent channel power	70dB
Audio harmonic distortion	Less than 10% (at 60% dev.)
Residual modulation	40dB
RECEIVER	
Sensitivity (at 20dB SINAD)	-2dBµ emf typ.
Squelch sensitivity	-6dBµ emf typ. (at threshold)
Adjacent channel selectivity	70dB
Spurious response	70dB
Intermodulation	68dB
Hum and noise	40dB
Audio output power (at 10% distortion, 8Ω load)	700mW typ. (Internal SP) 200mW (External SP)

## Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	-
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

## Applicable IP Rating

Ingress Protection Standard	
Water	IPX8 (Waterproof protection)

## OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

**BATTERY PACK**



**BP-245N** Li-Ion 7.4V, 1900mAh (min.), 2000mAh (typ.).

**RAPID CHARGER**



**BC-123SE**      **BC-210**

Charges the BP-245N in 2.5 hours (approx.).

**MULTI-CHARGER**



**BC-197**      **BC-157S**

Charges up to six BP-245N in 2.5 hours (approx.).  
AD-129 is supplied with the BC-197, depending on version.

**Supplied Accessories:**



- Cigarette lighter cable, CP-25H\*    • AC adapter, BC-123SE\*
- Rapid charger, BC-210    • Battery pack, BP-245N
- Belt clip, MB-103    • Antenna, FA-S59V or FA-S64V\*
- Hand strap

\* Not supplied or may differ depending on version.

**SPEAKER-MICROPHONES**



**HM-167**      **HM-202**

**BELT CLIPS**




**MB-86**      **MB-103**

**LEATHER BELT HANGERS**



**MB-96N**      **MB-96F**

**CIGARETTE LIGHTER CABLE & DC POWER CABLES**



**CP-25H** For use with BC-210

**OPC-515L** For use with BC-210

**OPC-656** For use with BC-197

**ANTENNAS**



**FA-S59V** (Left) 150mm  
**FA-S64V** (Right) 115mm

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries. AQUAQUAKE is a trademark of Icom Inc. (Japan) in the United States. All other trademarks are the properties of their respective holders.

**Icom Inc.** 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

[www.icom.co.jp/world](http://www.icom.co.jp/world) **Count on us!**

**Icom America Inc.**  
2380 116th Avenue NE,  
Bellevue, WA 98004, U.S.A.  
Phone : +1 (425) 454-8155  
Fax : +1 (425) 454-1509  
E-mail : sales@icomamerica.com  
URL : <http://www.icomamerica.com>

**Icom Canada**  
Glenwood Centre #150-6165 Highway 17,  
Delta, B.C., V4K 5B8, Canada  
Phone : +1 (604) 952-4266  
Fax : +1 (604) 952-0090  
E-mail : info@icomcanada.com  
URL : <http://www.icomcanada.com>

**Icom Brazil**  
Rua Pernambuco, 353 - Sala 901  
Belo Horizonte, M.G.  
30130-150, Brazil  
Phone : +55 (31) 3582 8847  
Fax : +55 (31) 3582 8987  
E-mail : sales@icombrasil.com

**Icom (Europe) GmbH**  
Communication Equipment  
Auf der Krautweide 24  
65812 Bad Soden am Taunus, Germany  
Phone : +49 (6196) 76685-0  
Fax : +49 (6196) 76685-50  
E-mail : info@icom-europe.com  
URL : <http://www.icomeurope.com>

**Icom Spain S.L.**  
Ctra. Rubi, No. 88 "Edificio Can Castanyer"  
Bajos A 08174, Sant Cugat del Valles,  
Barcelona, Spain  
Phone : +34 (93) 590 26 70  
Fax : +34 (93) 589 04 46  
E-mail : icom@icomspain.com  
URL : <http://www.icomspain.com>

**Icom Polska**  
81-850 Sopot, ul. 3 Maja 54, Poland  
Phone : +48 (58) 550 7135  
Fax : +48 (58) 551 0484  
E-mail : icompolska@icompolska.com.pl  
URL : <http://www.icompolska.com.pl>

**Icom (UK) Ltd.**  
Blacksole House, Altira Park,  
Herne Bay, Kent, CT6 6GZ, U.K.  
Phone : +44 (0) 1227 741741  
Fax : +44 (0) 1227 741742  
E-mail : info@icomuk.co.uk  
URL : <http://www.icomuk.co.uk>

**Icom France s.a.s.**  
Zac de la Plaine,  
1 Rue Brindejonc des Moulinais, BP 45804,  
31505 Toulouse Cedex 5, France  
Phone : +33 (5) 61 36 03 03  
Fax : +33 (5) 61 36 03 00  
E-mail : icom@icom-france.com  
URL : <http://www.icom-france.com>

**Icom (Australia) Pty. Ltd.**  
Unit 1 / 103 Garden Road,  
Clayton, VIC 3168 Australia  
Phone : +61 (03) 9549 7500  
Fax : +61 (03) 9549 7505  
E-mail : sales@icom.net.au  
URL : <http://www.icom.net.au>

**Icom New Zealand**  
146A Harris Road, East Tamaki,  
Auckland, New Zealand  
Phone : +64 (09) 274 4062  
Fax : +64 (09) 274 4708  
E-mail : inquiries@icom.co.nz  
URL : <http://www.icom.co.nz>

**Asia Icom Inc.**  
6F No. 68, Sec. 1 Cheng-Teh Road,  
Taipei, Taiwan, R.O.C.  
Phone : +886 (02) 2559 1899  
Fax : +886 (02) 2559 1874  
E-mail : sales@asia-icom.com  
URL : <http://www.asia-icom.com>

Your local distributor/dealer:

**SPRmarine  
Drumgelloch Business  
Centre  
Drumgelloch Street  
AIRDRIE  
ML6 7EW**

**E: info@SPRmarine.co.uk  
W: www.SPRmarine.co.uk**