

Specification for Rescue Laser Flare Magnum (RLFAA)													
Model	RLFAA – Rescue Laser Flare Magnum												
Wavelength	650nm												
Classification	CW, <5mW, Class IIIa final output power												
Power Supply	Two AA Batteries Approximate 72 operating hours per set of batteries												
Beam Shape	Collimated 5 deg. divergent laser line												
NOHD Nominal Ocular Hazard Distance	1mW output at 27", beam width 0.08"												
Operating Temp.	Typical -10 °C ~ +50°C												
Laser Operation	Twist cap laser activation												
Construction	Anodized 6061-T6 aluminum, waterproof to 80 feet (24m)												
Dimensions	5.69"(L) x 0.88"(dia.)												
Weight	2.85 oz. without batteries												
Dimension Drawing													
Product Label	<p>It is illegal to point this device at an aircraft except in an emergency!</p> <p>↑↑ LASER APERTURE ↑↑</p> <p>LASER RADIATION AVOID DIRECT EYE EXPOSURE CLASS 3R LASER PRODUCTS 530-680nm, 5mW cw max.</p> <p>Complies with: IEC/EN 60825-1, 2007-03 US DHHS 21 CFR Subchapter J</p> <p>Greatland Laser Rancho Cucamonga, CA, USA Model: Rescue Laser Flare® Magnum Manufactured: 2013 2014 2015</p> <table border="0"> <tr> <td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td> </tr> <tr> <td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td> </tr> </table> <p>Serial Number: RLFAA024-01 H00001 CE</p>	1	2	3	4	5	6	7	8	9	10	11	12
1	2	3	4	5	6								
7	8	9	10	11	12								